



Foamdoctor G2967

foam control agent

PennWhite

technical data sheet

foam control agents - general grade

Foamdoctor G2967 is a powerful foam control agent based on a blend of light mineral oil and non-ionic surfactants.

Foamdoctor G2967 controls foaming and aeration during paint manufacture, filling and application with a good compatibility in a wide range of solvent borne systems. It has a low viscosity for easy dispersibility with a long lasting efficiency.

TYPICAL PROPERTIES

Appearance:	Opaque, off white liquid
IR Spectra:	Conforms to reference
Viscosity:	150 – 350cP
Dispersion:	Disperses to a fine emulsion

APPLICATION

Foamdoctor G2967 should be agitated before use and can be pre-diluted for ease of application. Suggested dosage for some typical applications:

Application	Area	Dosage
Water based paints	Decorative	0.1 - 0.3%
	Coatings for public works, structural engineering	0.1 - 0.3%
Adhesives		0.05 - 0.3%
	Synthetic and Natural Latexes	0.1 - 0.3%
General Chemical Processing	Compounding and application	0.05 - 0.2%
	Dipping (anti-webbing)	100-500 ppm
	Waste water disposal	0.05 - 0.1%
	Distillation	0.1 - 0.3%
	Cleaning fluids	0.1 - 0.3%
	Printing pastes	0.1 - 0.2%
Agrochemicals	Wax emulsions	0.1 - 0.3%
	Decorative	0.1 - 0.3%

PACKAGING

Foamdoctor G2967 is available in 200kg drums.

SHELF LIFE AND STORAGE CONDITIONS

Keep container tightly closed. Store in a cool dry place between 5°C and 35°C. Protect from frost. Shelf life is 12 months in unopened containers.

(OPA2/F2)

TDS: 109

Issue: 03

Revised: 07/03/2014

Page 1 of 1

For additional technical or safety advice call us on 01606 734820 or email info@pennwhite.co.uk

PennWhite Ltd
Aston Way
Midpoint 18 Business Park
Middlewich, CW10 0HS



Telephone: +44 (0)1606 734820
Fax: +44 (0)1606 837867
Email: info@pennwhite.co.uk
Website: www.pennwhite.co.uk