



PennWhite

Foamdoctor G2968

foam control agent

technical data sheet

foam control agents - general grade

Foamdoctor G2968 is a powerful foam control agent based on a mixture of mineral oil and non-ionic surfactants.

Foamdoctor G2968 controls foaming and aeration during paint manufacture, filling and application with a good compatibility in a wide range of systems. It is effective over a wide pH range and retains a high and long lasting efficiency.

TYPICAL PROPERTIES

Appearance: Opaque, light brown, viscous liquid
Viscosity: 1000 – 3000cP

APPLICATION

Foamdoctor G2968 should be agitated before use and used without dilution. Suggested dosage for some typical applications:

Application	Area	Dosage
Water based paints	Matt paints	0.1 - 0.3%
	Silk and semi gloss paints	0.1 - 0.3%
Synthetic and Natural Lattices	Compounding and application	0.1 - 0.3%
	Dipping (anti-webbing)	0.05 - 0.2%
Adhesives	Starch, Dextrine, Casein	0.1 – 0.2%
	Acrylic, PV Acetate, PV Alcohol	0.1 – 0.3%
Water based paints	Matt paints	0.1 - 0.3%
	Silk and semi gloss paints	0.1 - 0.3%
Synthetic and Natural Lattices	Compounding and application	0.1 - 0.3%
	Dipping (anti-webbing)	0.05 - 0.2%

PACKAGING

Foamdoctor G2968 is available in 200kg drums and 1000kg IBCs.

SHELF LIFE AND STORAGE CONDITIONS

Keep container tightly closed. Store in a cool dry place between 5°C and 35°C. Shelf life is 12 months in unopened containers.

(OPA2/F2)

TDS: 111

Issue: 03

Revised: 07/03/2014

Page 1 of 1

For additional technical or safety advice call us on 01606 734820 or email info@pennwhite.co.uk

PennWhite Ltd

Aston Way

Midpoint 18 Business Park

Middlewich, CW10 0HS

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: info@pennwhite.co.uk

Website: www.pennwhite.co.uk

