



Foamdoctor G2975

foam control agent

PennWhite

technical data sheet

foam control agents - general grade

Foamdoctor G2975 is a powerful foam control agent based on a blend of polyethers and non-ionic surfactants.

Foamdoctor G2975 is mineral hydrocarbon free and has no adverse effect on printing rollers. It retains a very high efficiency and contains hydrophobised silica. **Foamdoctor G2975** also encourages the drainage and collapse of colloid stabilised foams.

TYPICAL PROPERTIES

Appearance:	Opaque, amber liquid
IR Spectra:	Conforms to reference
Viscosity:	300 – 1000cP

APPLICATION

Foamdoctor G2975 should be agitated before use and used without dilution. Suggested dosage for typical applications:

Application	Area	Dosage
Printing inks	Aqueous flexographic	0.1 – 0.3%
Paper coatings	Starch press	0.05 – 0.2%
Polyurethane dispersions		0.2 – 0.5%
Adhesives	Starch, dextrin, casein	0.1 – 0.2%
	Acrylic, PV acetate, PV alcohol	0.1 – 0.3%
Water treatment	Glycol separators	200 – 500ppm
Paint spray booths		0.05 – 0.2%

PACKAGING

Foamdoctor G2975 is available in 200kg drums and 1000kg IBC's.

SHELF LIFE AND STORAGE CONDITIONS

Keep container tightly closed. Store in a cool dry place between 5°C and 35°C. Shelf life is 12 months in unopened containers.

(OPA2/F2)

TDS: 113

Issue: 03

Revised: 07/03/2014

Page 1 of 1

For additional technical or safety advice call us on 01606 734820 or email info@pennwhite.co.uk

PennWhite Ltd
Aston Way
Midpoint 18 Business Park
Middlewich, CW10 0HS



Telephone: +44 (0)1606 734820
Fax: +44 (0)1606 837867
Email: info@pennwhite.co.uk
Website: www.pennwhite.co.uk