



PennWhite

# Foamdoctor G2967

foam control agent

## technical data sheet

**Foamdoctor G2967** is a powerful foam control agent based on a blend of light mineral oil and non ionic surfactants.

**Foamdoctor G2967** controls foaming and aeration during paint manufacture, filling and application with a good compatibility in a wide range of solvent borne systems. It has a low viscosity for easy dispersibility with a long lasting efficiency.

### TYPICAL PROPERTIES

Appearance:	Opaque, off white liquid
IR Spectra:	Conforms to reference
Viscosity:	150 – 350cP
Dispersion:	Disperses to a fine emulsion

### APPLICATION

**Foamdoctor G2967** should be agitated before use and can be pre-diluted for ease of application. Suggested dosage for some typical applications:

Application	Area	Dosage
Water based paints	Decorative	0.1 - 0.3%
	Coatings for public works, structural engineering	0.1 - 0.3%
Adhesives		0.05 - 0.3%
Synthetic and Natural Latices	Compounding and application	0.1 - 0.3%
	Dipping (anti-webbing)	0.05 - 0.2%
General Chemical Processing	Waste water disposal	100–500 ppm
	Distillation	0.05 - 0.1%
	Cleaning fluids	0.1 - 0.3%
	Printing pastes	0.1 - 0.3%
	Wax emulsions	0.1 - 0.2%
Agrochemicals		0.1 - 0.3%
Water based paints	Decorative	0.1 - 0.3%

### PACKAGING

**Foamdoctor G2967** is available in 200 kilo drums.

### SHELF LIFE AND STORAGE CONDITIONS

Keep container tightly closed. Store in a cool dry place between 5°C and 35°C. Protect from frost. Shelf life: 12 months in unopened containers.

(OPA2/F2)

TDS: 109

Issue: 02

Revised: 27/05/2010

Page 1 of 1

**For additional technical or safety advice call us on 01606 734820 or email [info@pennwhite.co.uk](mailto:info@pennwhite.co.uk)**

PennWhite Ltd

Aston Way

Midpoint 18 Business Park

Middlewich, CW10 0HS

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: [info@pennwhite.co.uk](mailto:info@pennwhite.co.uk)

Website: [www.pennwhite.co.uk](http://www.pennwhite.co.uk)

